

# DOTCO

## PORAKONEET ILMAN SUUNNANVAIHTOA

- 0.4 hp / 0.30 kW: 14CF-sarja
- 0.6 hp / 0.45 kW: 14CS-sarja
- 0.9 hp / 0.67 kW: 14CN-sarja
- Ergonominen kahvan muotoilu
- Loistava valinta moneen käyttökohteeseen

Nimike	Istukka	Kierrosnopeus rpm	Paino kg	Pituus mm
<b>14CF-sarjan porakoneet</b>				
14CFS97-38	1/4"	600	0,8	175,3
14CFS97-51	3/8"	600	0,8	175,3
14CFS97-40	3/8" - 24 E	600	0,8	175,3
14CFS96-38	1/4"	700	0,8	175,3
14CFS95-38	1/4"	1 000	0,8	175,3
14CFS95-51	3/8"	1 000	0,8	175,3
14CFS95-40	3/8" - 24 E	1 000	0,8	175,3
14CFS94-38	1/4"	2 400	0,7	144,8
14CFS94-40	3/8" - 24 E	2 400	0,7	144,8
14CFS93-38	1/4"	3 200	0,7	144,8
14CFS93-51	3/8"	3 200	0,7	144,8
14CFS93-40	3/8" - 24 E	3 200	0,7	144,8
14CFS92-38	1/4"	3 800	0,7	144,8
14CFS92-51	3/8"	3 800	0,7	144,8
14CFS91-38	1/4"	5 200	0,7	144,8
14CFS91-51	3/8"	5 200	0,7	144,8
14CFS90-38	1/4"	29 000	0,7	144,8
<b>14CS-sarjan porakoneet</b>				
14CSL97-40	3/8" - 24 E	500	1,3	205,7
14CSL97-51	3/8"	500	1,3	205,7
14CSL95-40	3/8" - 24 E	1 300	1,3	205,7
14CSL95-51	3/8"	1 300	1,3	205,7
14CSL92-38	1/4"	3 200	1,0	160,0
14CSL92-40	3/8" - 24 E	3 200	1,0	160,0
14CSL92-51	3/8"	3 200	0,95	160
14CSL91-38	1/4"	5 200	1,0	160,0
14CSL91-40	3/8" - 24 E	5 200	1,0	160,0
14CSL98-38	1/4"	6 000	1,0	160,0
14CSL98-40	3/8" - 24 E	6 000	1,0	160,0
14CSL90-38	1/4"	20 000	1,0	160,0

Nimike	Istukka	Kierrosnopeus rpm	Paino kg	Pituus mm
<b>14CN-sarjan porakoneet</b>				
14CNL97-51	3/8"	500	1,6	231,1
14CNL97-40	3/8" - 24 E	500	1,6	231,1
14CNL97-53	1/2"	500	1,6	231,1
14CNL95-51	3/8"	1 300	1,3	218,4
14CNL95-40	3/8" - 24 E	1 300	1,3	218,4
14CNL92-38	1/4"	3 200	1,1	182,9
14CNL92-51	3/8"	3 200	1,1	182,9
14CNL92-40	3/8" - 24 E	3 200	1,1	182,9
14CNL91-51	3/8"	5 200	1,1	182,9
14CNL91-40	3/8" - 24 E	5 200	1,1	182,9
14CNL98-38	1/4"	6 000	1,0	172,7
14CNL98-51	3/8"	6 000	1,0	172,7
14CNL98-53	1/2"	6 000	1,0	172,7
14CNL98-40	3/8" - 24 E	6 000	1,0	172,7
14CNL90-38	1/4"	20 000	1,0	172,7
14CNL90-40	3/8" - 24 E	20 000	1,0	172,7



14CF-sarja



14CS-sarja



14CN-sarja