

CLECO CELLCORE BATTERY POWERED NUTRUNNER

The Cleco CellCore battery powered nutrunner series offers a reliable solution for professional use in challenging conditions. The intelligent sensor-controlled nutrunners are designed to meet the changing needs of assembly work and withstand high usage rates. Special attention has been paid to the ergonomics, lightness, and weight distribution of the tools during the design process.

The interface of the wrenches allows tightening values to be set, even without a separate control unit if needed.



ANGLE MODELS

Item	Torque range Nm	Free speed rpm	Weight kg	Length mm	Height mm	Drive
CCBAW153(B)	4,5 - 15	570	1,70	456	88	3/8" SQ
CCBAW253(B)	7,5 - 25	305	1,70	456	88	3/8" SQ
CCBAW353(B)	10,5 - 35	255	1,95	486	92	3/8" SQ
CCBAW503(B)	15 - 50	165	2,00	499	92	3/8" SQ
CCBAW64S-11001	19 - 64	135	2,20	511	92	1/2" SQ
CCBAWN225NB6	45 - 225	34	4,7	610	260,4	3/4" SQ
CCBAWN750NB6	154 - 750	11	5,0	597	260,4	3/4" SQ
CCBAWN1000NB6	200 - 1000	7	5,0	610	260,4	3/4" SQ

*) Ball retainer

PISTOL MODELS

Item	Torque range Nm	Free speed rpm	Weight kg	Length mm	Height mm	Drive
CCBPW04Q	1,2 - 4	2 480	0,98	185	204	1/4" QC
CCBPW12Q	3,6 - 12	800	1,05	201	204	1/4" QC
CCBPW123	3,6 - 12	800	1,05	198	204	3/8" SQ
CCBPW22Q	6,6 - 22	430	1,05	201	204	1/4" QC
CCBPW223	6,6 - 22	430	1,05	198	204	3/8" SQ
CCBPWN200D6	40 - 195	42	3,36	339	204	3/4" SQ
CCBPWN500D6	119 - 500	14	3,58	339	204	3/4" SQ
CCBPWN1000D6	214 - 1000	8	6,38	403	208	3/4" SQ
CCBPWN1350D8	293 - 1350	6	6,68	403	208	1" SQ
CCBPWN2000D8	436 - 2000	4	7,23	403	208	1" SQ

ACCESSORIES

Item	Description
T50-1000497	18 V/2.0 Ah battery
T50-1000498	18 V/5.0 Ah battery
T50-1000506	18 V rapid charger
T50-1000508	18 V 6-bay charger



Item	Compatible
T50-1102352	CCBPW04Q
T50-1102353	CCBPW12Q, CCBPW123, CCBPW22Q, CCBPW223
T50-3102258	CCBAW153(B), CCBWA253(B), CCBWA353(B)
T50-3102259	CCBAW353(B)
T50-3102260	CCBAW503(B)

