

PNEUTORQUE STANDARD SERIES

STRAIGHT PNEUMATIC TORQUE WRENCHES

Straight model wrenches are available in single- and dual-speed versions (manual and automatic models) up to 300,000 Nm and are suitable for almost all applications.

FEATURES:

- All models include a direction switch
- Quiet operation with precise, consistent torque (non-impacting)
- Repeatability better than $\pm 5\%$
- Available models with integrated torque sensor
- Custom-designed special reaction arms available for specific applications
- Dual-speed models provide time savings and improved productivity
- The PT18 MTS model can be custom-designed for specific applications

Models are also available as remote-operated (remote) versions.

Model	Item	Torque Range Nm	Drive	Free Speed rpm	Length mm	Weight kg	Reaction Arm kg
Standard series - One Speed Models							
PT1	16031	160 - 680	3/4"	30	368	10,6	2,2
PT1	16011	160 - 680	1"	30	373	10,6	2,2
PT1A	16098	270 - 1 200	3/4"	15	368	11,1	2,2
PT1A	16097	270 - 1 200	1"	15	373	11,1	2,2
PT2	16013	515 - 1 700	1"	9	373	11,1	2,2
PT5	16015	880 - 3 400	1"	5	424	14,0	2,5
PT6	16017	880 - 3 400	1 1/2"	5	430	14,0	2,5
PT7	16066	1 762 - 6 000	1 1/2"	2.5	457	19,7	6,3
PT9	16072	2 710 - 9 500	1 1/2"	1.8	452	24,4	8,3
PT11	16046	4 400 - 20 000	2 1/2"	1.2	546	38,6	13,3
PT12	18086	9 500 - 34 000	2 1/2"	0.5	593	49,8	6,5
PT13	16052	13 550 - 47 000	2 1/2"	0.3	629	102,2	6,9
PT14	16045	22 375 - 100 000	3 1/2"	0.2	726	119,4	10,4
Standard series - Manual Two Speed							
PT1 MTS	16031.MTS	160 - 680	3/4"	150	454	14,1	2,2
PT1 MTS	16011.MTS	160 - 680	1"	150	459	14,1	2,2
PT1A MTS	16098.MTS	270 - 1 200	3/4"	75	454	14,6	2,2
PT1A MTS	16097.MTS	270 - 1 200	1"	75	459	14,6	2,2
PT2 MTS	16013.MTS	515 - 1 700	1"	45	459	14,6	2,2
PT5 MTS	16015.MTS	880 - 3 400	1"	25	510	17,5	2,5
PT6 MTS	16017.MTS	880 - 3 400	1 1/2"	25	516	17,5	2,5
PT7 MTS	16066.MTS	1 762 - 6 000	1 1/2"	12.5	543	23,2	6,3
PT9 MTS	16072.MTS	2 710 - 9 500	1 1/2"	9	538	27,9	8,3
PT11 MTS	16046.MTS	4 400 - 20 000	2 1/2"	6	632	42,1	13,3
PT12 MTS	18086.MTS	9 500 - 34 000	2 1/2"	2.5	679	53,3	6,5
PT13 MTS	16052.MTS	13 550 - 47 000	2 1/2"	1.5	716	105,7	6,9
PT14 MTS	16045.MTS	22 375 - 100 000	3 1/2"	1	800	122,9	10,4
PT18 MTS	16054.MTS	85 000 - 300 000	-	0.3	930	380,0	-
Standard series - Automatic Two Speed							
PT1 AUT	16031.AUT	160 - 680	3/4"	150	437	14,1	2,2
PT1 AUT	16011.AUT	160 - 680	1"	150	442	14,1	2,2
PT1A AUT	16098.AUT	270 - 1 200	3/4"	75	437	14,6	2,2
PT1A AUT	16097.AUT	270 - 1 200	1"	75	442	14,6	2,2
PT2 AUT	16013.AUT	515 - 1 700	1"	45	442	14,6	2,2
PT5 AUT	16015.AUT	880 - 3 400	1"	25	493	17,5	2,5
PT6 AUT	16017.AUT	880 - 3 400	1 1/2"	25	499	17,5	2,5
PT7 AUT	16066.AUT	1 762 - 6 000	1 1/2"	12.5	526	23,2	6,3
PT9 AUT	16072.AUT	2 710 - 9 500	1 1/2"	9	521	27,9	8,3



PT5

PT2



PT7 AUT

PT14 MTS



PT2 REMOTE