

TECNA BALANCERS

Repetitive movements strain and burden the body, even if the tool is light. With TECNA balancers, repetitive strain can be reduced, thus enhancing the user's endurance and efficiency. Balancers reduce tool impacts and extend their service life.

- Balancers widely available with a load range of 0.2 kg – 180 kg
- Cable length up to 3 m
- Cables available in three materials: Stainless steel, Nylon, and Pneumatic hose
- Manufactured according to DIN 15112 directive
- TECNA also offers alternative models for ESD, Food and ATEX environments

Model	Weight (kg)	Cable Length (mm)
Retractors		
Nylon housing	0,2 - 3	1 600
Pneumatic hose cable	0,4 - 5	900 - 1 350
Aluminium housing	0,2 - 14	1 600 - 2 500
ATEX models	0,2 - 14	1 600 - 2 500
ESD models	0,2 - 14	1 600 - 2 500
Automatic locking	0,5 - 14	2 000 - 2 500
Food industry	0,2 - 14	1 600 - 2 500
Zero Gravity		
ATEX Zero Gravity	4 - 100	2 000 - 2 700
ESD Zero Gravity	4 - 100	2 000 - 2 700
Zero Gravity	4 - 180	2 000 - 3 000



Retractor



Nylon housing



ATEX model



ESD model



Food industry



Zero Gravity



Zero Gravity with rubber cover



Pneumatic hose cable