

AIR PUMPS

PA SERIES

- ▮ Suitable for use with both single- and double-acting hydraulic cylinders
- ▮ Lightweight and corrosion-protected aluminum tanks
- ▮ Equipped with an internal overpressure valve
- ▮ Maximum allowable air pressure: 14 bar
- ▮ Maximum working pressure: 700 bar
- ▮ PA1500L- and PA3801L models equipped with remote control
- ▮ PA600- & PA600H (manual operation) models can be used in any position – mounting plate allows for secure installation, and 360° rotating hose fitting facilitates use in various positions

Item	Oil Capacity l	Output Flow Rate		Ports		Dimensions LxPxK mm	Weight kg
		Step 1 l/min	Step 2 l/min	Air	Oil		
Pumps For Single Acting Cylinders							
PA600	0,6	1,00	0,15	1/4"-18NPTF	3/8"-18NPTF	142 x 426 x 156	6,4
PA600H	0,6	1,00	0,15	1/4"-18NPTF	3/8"-18NPTF	146 x 426 x 114	5,7
PA1500	1,5	1,08	0,18	1/4"-18NPTF	3/8"-18NPTF	136 x 267 x 185	8,2
PA1500A*	1,5	1,08	0,18	1/4"-18NPTF	3/8"-18NPTF	136 x 267 x 185	8,2
PA1500L**	1,5	1,00	0,16	1/4"-18NPTF	3/8"-18NPTF	136 x 279 x 204	8,8
PA1500LA **,**	1,5	1,08	0,18	1/4"-18NPTF	3/8"-18NPTF	136 x 263 x 185	8,2
PA2000	2,0	1,07	0,20	1/4"-18NPTF	3/8"-18NPTF	152 x 294 x 207	9,1
PA3801	3,8	1,07	0,18	1/4"-18NPTF	3/8"-18NPTF	187 x 321 x 187	12,3
PA3801L**	3,8	1,00	0,16	1/4"-18NPTF	3/8"-18NPTF	187 x 321 x 207	13,8
PA7550	7,6	1,07	0,18	1/4"-18NPTF	3/8"-18NPTF	214 x 321 x 211	16,3
PA7550L**	7,6	1,07	0,18	1/4"-18NPTF	3/8"-18NPTF	214 x 321 x 211	16,3
Pumps For Double Acting Cylinders							
PA1500M	1,5	1,08	0,18	1/4"-18NPTF	3/8"-18NPTF	136 x 267 x 202	8,7
PA3801M	3,8	1,07	0,18	1/4"-18NPTF	3/8"-18NPTF	187 x 321 x 205	10,9
PA7550M	7,6	1,07	0,18	1/4"-18NPTF	3/8"-18NPTF	152 x 321 x 229	18,1
Rotary Pumps For Single Acting Cylinders							
PUARD1701	3,8	5,13	0,36	1/2"-NPT	3/8"-18NPTF	205 x 404 x 485	19
PUARD1703	11,4	5,13	0,30	1/2"-NPT	3/8"-18NPTF	305 x 456 x 304	25
PUARD4003	11,4	7,63	1,15	1/2"-NPT	3/8"-18NPTF	305 x 467 x 344	30
PUAR1703	11,4	6,83	0,36	1/2"-NPT	3/8"-18NPTF	305 x 459 x 267	25
PUAR4003	11,4	8,39	1,15	1/2"-NPT	3/8"-18NPTF	305 x 470 x 267	30
Rotary Pumps For Double Acting Cylinders							
PUARM1703	11,4	6,83	0,36	1/2"-NPT	3/8"-18NPTF	305 x 459 x 303	25
PUARM4003	11,4	8,39	1,15	1/2"-NPT	3/8"-18NPTF	305 x 470 x 344	27

*) Unit is equipped with an external pressure adjustment

***) These pumps are equipped with a hand held air powered pendant



PA600



PA1500



PA1500M



PUARD1701