

CLECO CELLTEK BATTERY POWERED NUTRUNNER

The Cleco CellTek battery powered nutrunner series is the optimal nutrunner solution for safety-critical assembly work. The intelligent, sensor-controlled nutrunners are designed to withstand high usage, offering durability, lightweight construction, and ergonomic weight distribution. The interface allows tightening values to be set, even without a separate control unit if needed.

CELLTEK NUTRUNNERS AVAILABLE WITH MPROCONNECT!

In the mProConnect model, the control unit is integrated directly into the tool, enabling quick deployment, reducing costs, and saving space. The tool connects directly to the MES system via Wi-Fi and Open Protocol, enabling real-time data transfer and easy updates and settings transfer via SD card without reprogramming.



ANGLE MODELS

Item	Torque range Nm	Free speed rpm	Weight kg	Lenght mm	Height mm	Drive
CTBAW153	3,6 - 15	1025	1,6	515	90	3/8" SQ
CTBAW213	5,2 - 21	735	1,6	515	90	3/8" SQ
CTBAW273	6,8 - 27	560	1,6	515	90	3/8" SQ
CTBAW383	10 - 38	395	1,65	526	90	3/8" SQ
CTBAW503	13 - 50	285	1,7	534	90	3/8" SQ
CTBAW653	17 - 65	220	1,8	543	90	3/8" SQ



PISTOL MODELS

Item	Torque range Nm	Free speed rpm	Weight kg	Lenght mm	Height mm	Drive
CTBPW05Q	1,1 - 4,9	3525	0,95	207	210	1/4" QC
CTBPW10Q	2,4 - 10	1600	1	207	210	1/4" QC
CTBPW15Q	3,4 - 14,4	1125	1	207	210	1/4" QC



ACCESSORIES

Item	Description
T50-1000497	18 V/2.0 Ah battery
T50-1000498	18 V/5.0 Ah battery
T50-1000506	18 V rapid charger
T50-1000508	18 V 6-bay charger



Item	Compatible
T50-1102725	CTBPW05Q
T50-1102726	CTBPW10Q, CTBPW15Q
T50-3102254	CTBAW153, CTBAW213, CTBAW273
T50-3102255	CTBAW383
T50-3102256	CTBAW503
T50-3102257	CTBAW653

